



BFP840ESD

Robust low noise Silicon Germanium Bipolar RF Transistor

Data Sheet

Revision 1.1, 2012-07-11

RF & Protection Devices

Edition 2012-07-11

Published by
Infineon Technologies AG
81726 Munich, Germany

© 2012 Infineon Technologies AG
All Rights Reserved.

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).

Warnings

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.

Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

BFP840ESD, Robust low noise Silicon Germanium Bipolar RF Transistor**Revision History: 2012-07-11, Revision 1.1**

Page	Subjects (major changes since last revision)
p. 9	RF input power changed from tbd to 20 dBm
p. 18	Figure 6 updated
p. 26	Chapter 'Simulation Data' added

Trademarks of Infineon Technologies AG

AURIX™, C166™, CanPAK™, CIPOST™, CIPURSE™, EconoPACK™, CoolMOS™, CoolSET™, CORECONTROL™, CROSSAVE™, DAVE™, DI-POL™, EasyPIM™, EconoBRIDGE™, EconoDUAL™, EconoPIM™, EconoPACK™, EiceDRIVER™, eupec™, FCOS™, HITFET™, HybridPACK™, I2RFT™, ISOFACE™, IsoPACK™, MIPAQ™, ModSTACK™, my-d™, NovalithIC™, OptiMOS™, ORIGA™, POWERCODE™; PRIMARION™, PrimePACK™, PrimeSTACK™, PRO-SIL™, PROFET™, RASIC™, ReverSave™, SatRIC™, SIEGET™, SINDRION™, SIPMOS™, SmartLEWIS™, SOLID FLASH™, TEMPFET™, thinQ!™, TRENCHSTOP™, TriCore™.

Other Trademarks

Advance Design System™ (ADS) of Agilent Technologies, AMBA™, ARM™, MULTI-ICE™, KEIL™, PRIMECELL™, REALVIEW™, THUMB™, µVision™ of ARM Limited, UK. AUTOSAR™ is licensed by AUTOSAR development partnership. Bluetooth™ of Bluetooth SIG Inc. CAT-iq™ of DECT Forum. COLOSSUS™, FirstGPS™ of Trimble Navigation Ltd. EMV™ of EMVCo, LLC (Visa Holdings Inc.). EPCOS™ of Epcos AG. FLEXGO™ of Microsoft Corporation. FlexRay™ is licensed by FlexRay Consortium. HYPERTERMINAL™ of Hilgraeve Incorporated. IEC™ of Commission Electrotechnique Internationale. IrDA™ of Infrared Data Association Corporation. ISO™ of INTERNATIONAL ORGANIZATION FOR STANDARDIZATION. MATLAB™ of MathWorks, Inc. MAXIM™ of Maxim Integrated Products, Inc. MICROTEC™, NUCLEUS™ of Mentor Graphics Corporation. MIPI™ of MIPI Alliance, Inc. MIPS™ of MIPS Technologies, Inc., USA. muRata™ of MURATA MANUFACTURING CO., MICROWAVE OFFICE™ (MWO) of Applied Wave Research Inc., OmniVision™ of OmniVision Technologies, Inc. Openwave™ Openwave Systems Inc. RED HAT™ Red Hat, Inc. RFMD™ RF Micro Devices, Inc. SIRIUS™ of Sirius Satellite Radio Inc. SOLARIS™ of Sun Microsystems, Inc. SPANSION™ of Spansion LLC Ltd. Symbian™ of Symbian Software Limited. TAIYO YUDEN™ of Taiyo Yuden Co. TEAKLITE™ of CEVA, Inc. TEKTRONIX™ of Tektronix Inc. TOKO™ of TOKO KABUSHIKI KAISHA TA. UNIX™ of X/Open Company Limited. VERILOG™, PALLADIUM™ of Cadence Design Systems, Inc. VLYNQ™ of Texas Instruments Incorporated. VXWORKS™, WIND RIVER™ of WIND RIVER SYSTEMS, INC. ZETEX™ of Diodes Zetex Limited.

Last Trademarks Update 2011-11-11

Table of Contents**Table of Contents**

Table of Contents	4
List of Figures	5
List of Tables	6
1 Product Brief	7
2 Features	8
3 Maximum Ratings	9
4 Thermal Characteristics	10
5 Electrical Characteristics	11
5.1 DC Characteristics	11
5.2 General AC Characteristics	11
5.3 Frequency Dependent AC Characteristics	12
5.4 Characteristic DC Diagrams	16
5.5 Characteristic AC Diagrams	19
6 Simulation Data	26
7 Package Information SOT343	27

List of Figures

Figure 1	Total Power Dissipation $P_{\text{tot}} = f(T_s)$	10
Figure 2	BFP840ESD Testing Circuit	12
Figure 3	Collector Current vs. Collector Emitter Voltage $I_C = f(V_{CE})$, I_B = Parameter	16
Figure 4	DC Current Gain $h_{FE} = f(I_C)$, $V_{CE} = 1.8$ V	16
Figure 5	Collector Current vs. Base Emitter Forward Voltage $I_C = f(V_{BE})$, $V_{CE} = 1.8$ V	17
Figure 6	Base Current vs. Base Emitter Forward Voltage $I_B = f(V_{BE})$, $V_{CE} = 1.8$ V	17
Figure 7	Base Current vs. Base Emitter Reverse Voltage $I_B = f(V_{EB})$, $V_{CE} = 1.8$ V	18
Figure 8	Transition Frequency $f_T = f(I_C)$, $f = 2$ GHz, V_{CE} = Parameter	19
Figure 9	3rd Order Intercept Point at output $OIP3 = f(I_C)$, $Z_S = Z_L = 50 \Omega$, V_{CE} , f = Parameters	19
Figure 10	3rd Order Intercept Point at output $OIP3$ [dBm] = $f(I_C, V_{CE})$, $Z_S = Z_L = 50 \Omega$, $f = 5.5$ GHz	20
Figure 11	Compression Point at output $OP_{1\text{dB}}$ [dBm] = $f(I_C, V_{CE})$, $Z_S = Z_L = 50 \Omega$, $f = 5.5$ GHz	20
Figure 12	Collector Base Capacitance $C_{CB} = f(V_{CB})$, $f = 1$ MHz	21
Figure 13	Gain $G_{\text{ma}}, G_{\text{ms}}, S_{21} ^2 = f(f)$, $V_{CE} = 1.8$ V, $I_C = 10$ mA	21
Figure 14	Maximum Power Gain $G_{\text{max}} = f(I_C)$, $V_{CE} = 1.8$ V, f = Parameter in GHz	22
Figure 15	Maximum Power Gain $G_{\text{max}} = f(V_{CE})$, $I_C = 10$ mA, f = Parameter in GHz	22
Figure 16	Input Reflection Coefficient $S_{11} = f(f)$, $V_{CE} = 1.8$ V, $I_C = 5 / 10 / 15$ mA	23
Figure 17	Source Impedance for Minimum Noise Figure $Z_{\text{opt}} = f(f)$, $V_{CE} = 1.8$ V, $I_C = 5 / 10 / 15$ mA	23
Figure 18	Output Reflection Coefficient $S_{22} = f(f)$, $V_{CE} = 1.8$ V, $I_C = 5 / 10 / 15$ mA	24
Figure 19	Noise Figure $NF_{\text{min}} = f(f)$, $V_{CE} = 1.8$ V, $I_C = 5 / 10 / 15$ mA, $Z_S = Z_{\text{opt}}$	24
Figure 20	Noise Figure $NF_{\text{min}} = f(I_C)$, $V_{CE} = 1.8$ V, $Z_S = Z_{\text{opt}}$, f = Parameter in GHz	25
Figure 21	Noise Figure $NF_{50} = f(I_C)$, $V_{CE} = 1.8$ V, $Z_S = 50 \Omega$, f = Parameter in GHz	25
Figure 22	Package Outline	27
Figure 23	Package Foot Print	27
Figure 24	Marking Example (Marking BFP840ESD: T8s)	27
Figure 25	Tape Dimensions	27

List of Tables

Table 1	Maximum Ratings at $T_A = 25^\circ\text{C}$ (unless otherwise specified)	9
Table 2	Thermal Resistance	10
Table 3	DC Characteristics at $T_A = 25^\circ\text{C}$	11
Table 4	General AC Characteristics at $T_A = 25^\circ\text{C}$	11
Table 5	AC Characteristics, $V_{CE} = 1.8 \text{ V}, f = 0.45 \text{ GHz}$	12
Table 6	AC Characteristics, $V_{CE} = 1.8 \text{ V}, f = 0.9 \text{ GHz}$	12
Table 7	AC Characteristics, $V_{CE} = 1.8 \text{ V}, f = 1.5 \text{ GHz}$	13
Table 8	AC Characteristics, $V_{CE} = 1.8 \text{ V}, f = 1.9 \text{ GHz}$	13
Table 9	AC Characteristics, $V_{CE} = 1.8 \text{ V}, f = 2.4 \text{ GHz}$	14
Table 10	AC Characteristics, $V_{CE} = 1.8 \text{ V}, f = 3.5 \text{ GHz}$	14
Table 11	AC Characteristics, $V_{CE} = 1.8 \text{ V}, f = 5.5 \text{ GHz}$	14
Table 12	AC Characteristics, $V_{CE} = 1.8 \text{ V}, f = 10 \text{ GHz}$	15
Table 13	AC Characteristics, $V_{CE} = 1.8 \text{ V}, f = 12 \text{ GHz}$	15

1 Product Brief

The BFP840ESD is a high performance HBT (Heterojunction Bipolar Transistor) specifically designed for 5-6 GHz WiFi applications. The device is based upon the reliable high volume SiGe:C technology of Infineon.

The BFP840ESD provides inherently good input and output power match as well as inherently good noise match at 5-6 GHz. The simultaneous noise and power match without lossy external matching components at the input leads to a low external parts count, to a very good noise figure and to a very high transducer gain in the WiFi application. Integrated protection elements at in- and output make the device robust against ESD and excessive RF input power.


The device offers its high performance at low current and voltage and is especially well-suited for portable battery-powered applications in which energy efficiency is a key requirement. The device comes in an easy to use industry standard package with visible leads.

Robust very low noise SiGe:C Bipolar NPN RF Transistor in easy to use industry standard package

BFP840ESD

2 Features

- Robust very low noise amplifier based on Infineon's reliable, high volume SiGe:C technology
- Unique combination of high end RF performance and robustness: 20 dBm maximum RF input power, 1.5 kV HBM ESD hardness
- Very high transition frequency $f_T = 80$ GHz enables very low noise figure at high frequencies: $NF_{min} = 0.85$ dB at 5.5 GHz, 1.8 V, 6 mA
- High gain $|S_{21}|^2 = 18.5$ dB at 5.5 GHz, 1.8 V, 10 mA
- $OIP3 = 23$ dBm at 5.5 GHz, 1.5 V, 6 mA
- Ideal for low voltage applications e.g. $V_{CC} = 1.2$ V and 1.8 V (2.85 V, 3.3 V, 3.6 V requires corresponding collector resistor)
- Low power consumption, ideal for mobile applications
- Easy to use Pb free (RoHS compliant) and halogen free industry standard package with visible leads



Applications

As Low Noise Amplifier (LNA) in

- Mobile and fixed connectivity applications: WLAN 802.11, WiMAX and UWB
- Satellite communication systems: satellite radio (SDARs, DAB), navigation systems (e.g. GPS, Glonass) and C-band LNB (1st and 2nd stage LNA)
- Ku-band LNB front-end (2nd stage or 3rd stage LNA and active mixer)
- Ka-band oscillators (DROs)

Attention: ESD (Electrostatic discharge) sensitive device, observe handling precautions

Product Name	Package	Pin Configuration				Marking
BFP840ESD	SOT343	1 = B	2 = E	3 = C	4 = E	T8s

3 Maximum Ratings

Table 1 Maximum Ratings at $T_A = 25^\circ\text{C}$ (unless otherwise specified)

Parameter	Symbol	Values		Unit	Note / Test Condition
		Min.	Max.		
Collector emitter voltage	V_{CEO}	—	2.25 2.0	V	$T_A = 25^\circ\text{C}$ $T_A = -55^\circ\text{C}$ Open base
Collector emitter voltage ¹⁾	V_{CES}	—	2.25 2.0	V	$T_A = 25^\circ\text{C}$ $T_A = -55^\circ\text{C}$ E-B short circuited
Collector base voltage ²⁾	V_{CBO}	—	2.9 2.6	V	$T_A = 25^\circ\text{C}$ $T_A = -55^\circ\text{C}$ Open emitter
Base current	I_B	-5	3	mA	—
Collector current	I_C	—	35	mA	—
RF input power	P_{RFin}	—	20	dBm	—
ESD stress pulse	V_{ESD}	-1.5	1.5	kV	HBM, all pins, acc. to JESD22-A114
Total power dissipation ³⁾	P_{tot}	—	75	mW	$T_S \leq 108^\circ\text{C}$
Junction temperature	T_J	—	150	°C	—
Storage temperature	T_{Sg}	-55	150	°C	—

1) V_{CES} is identical to V_{CEO} due to design

2) V_{CBO} is similar to V_{CEO} due to design

3) T_S is the soldering point temperature. T_S is measured on the emitter lead at the soldering point of the pcb.

**Attention: Stresses above the max. values listed here may cause permanent damage to the device.
Exposure to absolute maximum rating conditions for extended periods may affect device reliability. Maximum ratings are absolute ratings; exceeding only one of these values may cause irreversible damage to the integrated circuit.**

4 Thermal Characteristics

Table 2 Thermal Resistance

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Junction - soldering point ¹⁾	R_{thJS}	–	551	–	K/W	–

1) For calculation of R_{thJA} please refer to Application Note Thermal Resistance AN 077




Figure 1 Total Power Dissipation $P_{tot} = f(T_s)$

5 Electrical Characteristics

5.1 DC Characteristics

Table 3 DC Characteristics at $T_A = 25^\circ\text{C}$

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Collector emitter breakdown voltage	$V_{(\text{BR})\text{CEO}}$	2.25	2.6	—	V	$I_C = 1 \text{ mA}, I_B = 0$ Open base
Collector emitter leakage current	I_{CES}	—	—	400	nA	$V_{\text{CE}} = 1.5 \text{ V}, V_{\text{BE}} = 0$ E-B short circuited
Collector base leakage current	I_{CBO}	—	—	400	nA	$V_{\text{CB}} = 1.5 \text{ V}, I_E = 0$ Open emitter
Emitter base leakage current	I_{EBO}	—	—	10	μA	$V_{\text{EB}} = 0.5 \text{ V}, I_C = 0$ Open collector
DC current gain	h_{FE}	150	260	450		$V_{\text{CE}} = 1.8 \text{ V}, I_C = 10 \text{ mA}$ Pulse measured

5.2 General AC Characteristics

Table 4 General AC Characteristics at $T_A = 25^\circ\text{C}$

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Transition frequency	f_T	—	80	—	GHz	$V_{\text{CE}} = 1.8 \text{ V}, I_C = 25 \text{ mA}$ $f = 2 \text{ GHz}$
Collector base capacitance	C_{CB}	—	37	—	fF	$V_{\text{CB}} = 1.8 \text{ V}, V_{\text{BE}} = 0$ $f = 1 \text{ MHz}$ Emitter grounded
Collector emitter capacitance	C_{CE}	—	0.40	—	pF	$V_{\text{CE}} = 1.8 \text{ V}, V_{\text{BE}} = 0$ $f = 1 \text{ MHz}$ Base grounded
Emitter base capacitance	C_{EB}	—	0.41	—	pF	$V_{\text{EB}} = 0.4 \text{ V}, V_{\text{CB}} = 0$ $f = 1 \text{ MHz}$ Collector grounded

5.3 Frequency Dependent AC Characteristics

Measurement setup is a test fixture with Bias T's in a 50Ω system, $T_A = 25^\circ\text{C}$




Figure 2 BFP840ESD Testing Circuit

Table 5 AC Characteristics, $V_{CE} = 1.8 \text{ V}$, $f = 0.45 \text{ GHz}$

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Power gain					dB	
Maximum power gain	G_{ms}	—	33.5	—		$I_C = 10 \text{ mA}$
Transducer gain	$ S_{21} ^2$	—	27.5	—		$I_C = 10 \text{ mA}$
Minimum Noise Figure					dB	
Minimum noise figure	NF_{min}	—	0.6	—		$I_C = 5 \text{ mA}$
Associated gain	G_{ass}	—	26.5	—		$I_C = 5 \text{ mA}$
Linearity					dBm	
1 dB compression point at output	$OP_{1\text{dB}}$	—	4	—		$Z_S = Z_L = 50 \Omega$
3rd order intercept point at output	$OIP3$	—	19.5	—		$I_C = 10 \text{ mA}$

Table 6 AC Characteristics, $V_{CE} = 1.8 \text{ V}$, $f = 0.9 \text{ GHz}$

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Power gain					dB	
Maximum power gain	G_{ms}	—	30	—		$I_C = 10 \text{ mA}$
Transducer gain	$ S_{21} ^2$	—	27	—		$I_C = 10 \text{ mA}$

Electrical Characteristics

Table 6 AC Characteristics, $V_{CE} = 1.8 \text{ V}, f = 0.9 \text{ GHz}$ (cont'd)

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Minimum Noise Figure						
Minimum noise figure	NF_{min}	—	0.6	—	dB	$I_C = 5 \text{ mA}$
Associated gain	G_{ass}	—	25.5	—		$I_C = 5 \text{ mA}$
Linearity						
1 dB compression point at output	OP_{1dB}	—	4	—	dBm	$Z_S = Z_L = 50 \Omega$
3rd order intercept point at output	$OIP3$	—	19.5	—		$I_C = 10 \text{ mA}$

Table 7 AC Characteristics, $V_{CE} = 1.8 \text{ V}, f = 1.5 \text{ GHz}$

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Power gain						
Maximum power gain	G_{ms}	—	28	—	dB	$I_C = 10 \text{ mA}$
Transducer gain	$ S_{21} ^2$	—	25.5	—		$I_C = 10 \text{ mA}$
Minimum Noise Figure						
Minimum noise figure	NF_{min}	—	0.65	—	dB	$I_C = 5 \text{ mA}$
Associated gain	G_{ass}	—	24	—		$I_C = 5 \text{ mA}$
Linearity						
1 dB compression point at output	OP_{1dB}	—	4.0	—	dBm	$Z_S = Z_L = 50 \Omega$
3rd order intercept point at output	$OIP3$	—	19.5	—		$I_C = 10 \text{ mA}$

Table 8 AC Characteristics, $V_{CE} = 1.8 \text{ V}, f = 1.9 \text{ GHz}$

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Power gain						
Maximum power gain	G_{ms}	—	27	—	dB	$I_C = 10 \text{ mA}$
Transducer gain	$ S_{21} ^2$	—	25	—		$I_C = 10 \text{ mA}$
Minimum Noise Figure						
Minimum noise figure	NF_{min}	—	0.65	—	dB	$I_C = 5 \text{ mA}$
Associated gain	G_{ass}	—	23	—		$I_C = 5 \text{ mA}$
Linearity						
1 dB compression point at output	OP_{1dB}	—	4.5	—	dBm	$Z_S = Z_L = 50 \Omega$
3rd order intercept point at output	$OIP3$	—	21	—		$I_C = 10 \text{ mA}$

Electrical Characteristics

Table 9 AC Characteristics, $V_{CE} = 1.8 \text{ V}$, $f = 2.4 \text{ GHz}$

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Power gain					dB	
Maximum power gain	G_{ms}	—	26	—		$I_C = 10 \text{ mA}$
Transducer gain	$ S_{21} ^2$	—	24	—		$I_C = 10 \text{ mA}$
Minimum Noise Figure					dB	
Minimum noise figure	NF_{min}	—	0.7	—		$I_C = 5 \text{ mA}$
Associated gain	G_{ass}	—	22	—		$I_C = 5 \text{ mA}$
Linearity					dBm	
1 dB compression point at output	$OP_{1\text{dB}}$	—	4	—		$I_C = 10 \text{ mA}$
3rd order intercept point at output	$OIP3$	—	21	—		$I_C = 10 \text{ mA}$

Table 10 AC Characteristics, $V_{CE} = 1.8 \text{ V}$, $f = 3.5 \text{ GHz}$

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Power gain					dB	
Maximum power gain	G_{ms}	—	24.5	—		$I_C = 10 \text{ mA}$
Transducer gain	$ S_{21} ^2$	—	22	—		$I_C = 10 \text{ mA}$
Minimum Noise Figure					dB	
Minimum noise figure	NF_{min}	—	0.7	—		$I_C = 5 \text{ mA}$
Associated gain	G_{ass}	—	20	—		$I_C = 5 \text{ mA}$
Linearity					dBm	
1 dB compression point at output	$OP_{1\text{dB}}$	—	5	—		$I_C = 10 \text{ mA}$
3rd order intercept point at output	$OIP3$	—	22.5	—		$I_C = 10 \text{ mA}$

Table 11 AC Characteristics, $V_{CE} = 1.8 \text{ V}$, $f = 5.5 \text{ GHz}$

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Power gain					dB	
Maximum power gain	G_{ma}	—	22.5	—		$I_C = 10 \text{ mA}$
Transducer gain	$ S_{21} ^2$	—	18.5	—		$I_C = 10 \text{ mA}$
Minimum Noise Figure					dB	
Minimum noise figure	NF_{min}	—	0.85	—		$I_C = 5 \text{ mA}$
Associated gain	G_{ass}	—	17	—		$I_C = 5 \text{ mA}$
Linearity					dBm	
1 dB compression point at output	$OP_{1\text{dB}}$	—	5	—		$I_C = 10 \text{ mA}$
3rd order intercept point at output	$OIP3$	—	22	—		$I_C = 10 \text{ mA}$

Electrical Characteristics

Table 12 AC Characteristics, $V_{CE} = 1.8 \text{ V}$, $f = 10 \text{ GHz}$

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Power gain						
Maximum power gain	G_{ms}	—	17	—	dB	$I_C = 10 \text{ mA}$
Transducer gain	$ S_{21} ^2$	—	12	—		$I_C = 10 \text{ mA}$
Minimum Noise Figure						
Minimum noise figure	NF_{min}	—	1.2	—	dB	$I_C = 5 \text{ mA}$
Associated gain	G_{ass}	—	12.5	—		$I_C = 5 \text{ mA}$
Linearity						
1 dB compression point at output	$OP_{1\text{dB}}$	—	2.5	—	dBm	$Z_S = Z_L = 50 \Omega$
3rd order intercept point at output	$OIP3$	—	19.5	—		$I_C = 10 \text{ mA}$
						$I_C = 10 \text{ mA}$

Table 13 AC Characteristics, $V_{CE} = 1.8 \text{ V}$, $f = 12 \text{ GHz}$

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Power gain						
Maximum power gain	G_{ms}	—	15.5	—	dB	$I_C = 10 \text{ mA}$
Transducer gain	$ S_{21} ^2$	—	9.5	—		$I_C = 10 \text{ mA}$
Minimum Noise Figure						
Minimum noise figure	NF_{min}	—	1.45	—	dB	$I_C = 5 \text{ mA}$
Associated gain	G_{ass}	—	11	—		$I_C = 5 \text{ mA}$
Linearity						
1 dB compression point at output	$OP_{1\text{dB}}$	—	1.5	—	dBm	$Z_S = Z_L = 50 \Omega$
3rd order intercept point at output	$OIP3$	—	18.5	—		$I_C = 10 \text{ mA}$
						$I_C = 10 \text{ mA}$

Note:

1. *OIP3 value depends on the termination of all intermodulation frequency components. The termination used for this measurement is 50Ω from 0.2 MHz to 12 GHz.*

5.4 Characteristic DC Diagrams




Figure 3 Collector Current vs. Collector Emitter Voltage $I_C = f(V_{CE})$, I_B = Parameter




Figure 4 DC Current Gain $h_{FE} = f(I_C)$, $V_{CE} = 1.8\text{ V}$


Electrical Characteristics


Figure 5 Collector Current vs. Base Emitter Forward Voltage $I_C = f(V_{BE})$, $V_{CE} = 1.8$ V




Figure 6 Base Current vs. Base Emitter Forward Voltage $I_B = f(V_{BE})$, $V_{CE} = 1.8$ V

Electrical Characteristics




Figure 7 Base Current vs. Base Emitter Reverse Voltage $I_B = f(V_{EB})$, $V_{CE} = 1.8 \text{ V}$

5.5 Characteristic AC Diagrams




Figure 8 Transition Frequency $f_T = f(I_C)$, $f = 2$ GHz, V_{CE} = Parameter




Figure 9 3rd Order Intercept Point at output $OIP3 = f(I_C)$, $Z_S = Z_L = 50 \Omega$, V_{CE}, f = Parameters


Electrical Characteristics


Figure 10 3rd Order Intercept Point at output $OIP3 \text{ [dBm]} = f(I_C, V_{CE})$, $Z_S = Z_L = 50 \Omega, f = 5.5 \text{ GHz}$




Figure 11 Compression Point at output $OP_{1\text{dB}} \text{ [dBm]} = f(I_C, V_{CE})$, $Z_S = Z_L = 50 \Omega, f = 5.5 \text{ GHz}$

Electrical Characteristics




Figure 12 Collector Base Capacitance $C_{CB} = f(V_{CB})$, $f = 1 \text{ MHz}$




Figure 13 Gain G_{ma} , G_{ms} , $|S_{21}|^2 = f(f)$, $V_{CE} = 1.8 \text{ V}$, $I_C = 10 \text{ mA}$


Electrical Characteristics


Figure 14 Maximum Power Gain $G_{\max} = f(I_C)$, $V_{CE} = 1.8$ V, f = Parameter in GHz




Figure 15 Maximum Power Gain $G_{\max} = f(V_{CE})$, $I_C = 10$ mA, f = Parameter in GHz


Electrical Characteristics


Figure 16 Input Reflection Coefficient $S_{11} = f(f)$, $V_{CE} = 1.8 \text{ V}$, $I_C = 5 / 10 / 15 \text{ mA}$




Figure 17 Source Impedance for Minimum Noise Figure $Z_{\text{opt}} = f(f)$, $V_{CE} = 1.8 \text{ V}$, $I_C = 5 / 10 / 15 \text{ mA}$


Electrical Characteristics


Figure 18 Output Reflection Coefficient $S_{22} = f(f)$, $V_{CE} = 1.8 \text{ V}$, $I_C = 5 / 10 / 15 \text{ mA}$




Figure 19 Noise Figure $NF_{\min} = f(f)$, $V_{CE} = 1.8 \text{ V}$, $I_C = 5 / 10 / 15 \text{ mA}$, $Z_S = Z_{\text{opt}}$

Electrical Characteristics




Figure 20 Noise Figure $NF_{min} = f(I_C)$, $V_{CE} = 1.8\text{ V}$, $Z_S = Z_{opt}$, f = Parameter in GHz




Figure 21 Noise Figure $NF_{50} = f(I_C)$, $V_{CE} = 1.8\text{ V}$, $Z_S = 50\Omega$, f = Parameter in GHz

Note: The curves shown in this chapter have been generated using typical devices but shall not be considered as a guarantee that all devices have identical characteristic curves. $T_A = 25^\circ\text{C}$.

6 Simulation Data

For the SPICE Gummel Poon (GP) model as well as for the S-parameters (including noise parameters) please refer to our internet website. Please consult our website and download the latest versions before actually starting your design.

You find the BFP840ESD SPICE GP model in the internet in MWO- and ADS-format, which you can import into these circuit simulation tools very quickly and conveniently. The model already contains the package parasitics and is ready to use for DC and high frequency simulations. The terminals of the model circuit correspond to the pin configuration of the device.

The model parameters have been extracted and verified up to 12 GHz using typical devices. The BFP840ESD SPICE GP model reflects the typical DC- and RF-performance within the limitations which are given by the SPICE GP model itself. Besides the DC characteristics all S-parameters in magnitude and phase, as well as noise figure (including optimum source impedance, equivalent noise resistance and flicker noise) and intermodulation have been extracted.

7 Package Information SOT343




Figure 22 Package Outline




Figure 23 Package Foot Print




Figure 24 Marking Example (Marking BFP840ESD: T8s)




Figure 25 Tape Dimensions

www.infineon.com